



PANELS

WC1500/CR COMPUTER ROOM PANEL:

The combination of heavy duty wood core strength and steel outer sheets have made this a superior and flexible panel to meet every building requirement.

The WC Series panel combines a die cut galvanized steel top sheet and die cut formed bottom pan that are structurally bonded to the high density composite core with thermo setting adhesives. The surface covering is typically a high pressure laminate, or reinforced vinyl. All panels employ a mechanically locked trim. A positive plenum seal is created by identical panel squareness and a conductive vinyl stringer gasket.

WC1500/GO GENERAL OFFICE PANEL:

The combination of heavy duty wood core and steel outer sheets provide superior acoustics.

The surface preparation is typically bare. Cornerlock design in conjunction with the high density composite core provides slab like underfoot performance.

PANEL TYPE	1500/CR IMPERIAL	1500/CR METRIC		1500/GO IMPERIAL	1500/GO METRIC
Concentrated Load*	1500 lbs.	6.16 kN		1500 lbs.	6.6 kN
Uniform Load**	400 lbs.	182 kg.		400 lbs.	182 kg.
Rolling Load ***	1500 lbs./1000 lbs.	680 kg./454 kg.		1250 lbs./800 lbs.	566 kg./363 kg.
Minimum Ultimate Load*	3000 lbs.	1363 kg.		2800 lbs.	1273 kg.
Size	24" x 24"	600 mm x 600 mm		24" x 24"	600 mm x 600 mm
Finished Floor Heights	3" to 60"	75 mm to 1500 mm		2 1/2" to 24"	75 mm to 600 mm
Understructure	Bolted Stringer	Bolted Stringer		Cornerlock	Cornerlock
Floor Finishes	High pressure Laminate Conductive Vinyl	High pressure Laminate Conductive Vinyl		Free lay carpet tile Factory bonded carpet	Free lay carpet tile Factory bonded carpet

* Measured on 1 sq.in. or 25 mm².

**Measured on 1 sq.ft. or 30 cm x 30 cm area.

*** 3" diameter (76mm) x 1 13/16" wide (46mm) wheel / 6" x 1 1/2" wide wheel. CISCA